AeroBas Grou

View Online at https://aerobasegroup.com/nsn/5935-01-289-7358

Body Style:

Straight type

Overall Length:

6.150 inches

Overall Height:

0.605 inches

Overall Width:

0.250 inches

Environmental Protection:

Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

5.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand at 3 oclock and d shape pin right-hand at 3 oclock

Electrical Receptacle Connector - Page 2 of 2



 Insert Material Specification:

 Mil-m-14g, ty gdi-30f or sdg-f military specification all material responses single mating end

 Included Contact Quantity:

 100 single mating end single contact grouping

 Included Contact Type:

 Round socket single mating end single contact grouping

 Precious Material And Location:

 Contact surfaces gold

 Precious Material And Weight:

 0.100 gold grains, troy

 Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.