## NSN 5935-01-289-7363

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-289-7363

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.263 inches

**Overall Height:** 

Between 1.792 inches and 1.832 inches

Overall Width:

Between 1.792 inches and 1.832 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.142 inches and 0.157 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 

1.500 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.597 inches and 0.602 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

24-19 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-289-7363

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
ncluded Contact Quantity:
19 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27466 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.