Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-290-0579

Body Style:

Straight shape, external coupling

Overall Length:

1.709 inches

Overall Height:

1.587 inches

Overall Width:

1.587 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 2

federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

NSN 5935-01-290-0579

Electrical Receptacle Connector - Page 2 of 2

Aero	Base
	Group

Shell Surface Treatment:	
Cadmium and chromate	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification all treatment responses	
Shell Material Specification:	
Qq-a-591 federal specification single material response	
Included Contact Quantity:	
6 single mating end 2nd contact grouping	
Included Contact Type:	
Round pin single mating end all contact groupings	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.010 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	