## NSN 5935-01-290-2373

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-290-2373

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 1.111 inches and 1.183 inches

**Overall Diameter:** 

Between 1.714 inches and 1.746 inches

**Environmental Protection:** 

Corrosion resistant and moisture resistant

**Distance From Mounting Shoulder To Front Face:** 

Between 0.786 inches and 0.818 inches

**Mounting Facility Thickness:** 

Between 0.062 inches and 0.109 inches

**Threaded Device Type:** 

Back shell and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-37 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

110.0

Shell Type:

Solid

**Connector Locking Method:** 

Detent

**Thread Length:** 

0.219 inches

Thready Qty Per Inch (tpi):

20 and 18

**Thread Size:** 

0.812 inches and 1.250 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

## NSN 5935-01-290-2373

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Glass single mating end and plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Included Contact Quantity:
34 single mating end 3rd contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.049 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military

Mil-std (military Standard):

Mil-g-45204 spec.