

View Online at <https://aerobasegroup.com/nsn/5935-01-290-4817>

**Body Style:**

Right angle type

**Overall Length:**

0.810 inches

**Overall Width:**

0.520 inches

**Body Height:**

0.335 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**End Application:**

Forrestal class cv, nimitz class cvn, arleigh burke class ddg, ticonderoga class cg (47), kidd class ddg, spruance class dd (963).

Tf33-pw-102 engine c-135e, ec-135h/k/p aircraft. Consolidated space operations center. Landing craft air cushion (lcac).

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Pin single mating end single contact grouping

**Included Contact Quantity:**

10 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.