NSN 5935-01-291-2861

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length:

Rectangular shape center screwlock

Between 2.770 inches and 2.790 inches

2b

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-291-2861

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.450 inches and 2.470 inches **Overall Height:** Between 0.780 inches and 0.800 inches **Overall Width:** Between 0.510 inches and 0.530 inches **Unthreaded Mounting Hole Diameter:** Between 0.120 inches and 0.130 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

NSN 5935-01-291-2861

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30-f or ty sdg-f military specification all material responses single mating end

Included Contact Quantity:

88 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.088 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.