NSN 5935-01-291-9113

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-291-9113

| Thread Class: |
|--|
| 2b and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.935 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 0.308 inches |
| Distance Between Mounting Facility Centers: |
| Between 0.710 inches and 0.720 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 15 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 56 and 56 |
| Thread Size: |
| 0.086 inches and 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Glass fiber single mating end and plastic diallyl phthalate single mating end or plastic polyester single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |

reminar Type.

Crimp single mating end single contact grouping

NSN 5935-01-291-9113

Shell Material:

Electrical Receptacle Connector - Page 2 of 2



| Aluminum alloy |
|--|
| Shell Surface Treatment: |
| Nickel |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-14, ty sdg-f military specification 2nd material |
| response single mating end or mil-m-24519 military specification 3rd material response single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 15 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Jackscrew type-female and location-left handandjackscrew type-female and location-right hand |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.015 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |
| |