NSN 5935-01-291-9113

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-291-9113

Thread Class:
2b and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
0.935 inches
Overall Height:
0.500 inches
Overall Width:
0.308 inches
Distance Between Mounting Facility Centers:
Between 0.710 inches and 0.720 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56
Thread Size:
0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass fiber single mating end and plastic diallyl phthalate single mating end or plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

reminar Type.

Crimp single mating end single contact grouping

NSN 5935-01-291-9113

Shell Material:

Electrical Receptacle Connector - Page 2 of 2



Aluminum alloy
Shell Surface Treatment:
Nickel
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-14, ty sdg-f military specification 2nd material
response single mating end or mil-m-24519 military specification 3rd material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.