NSN 5935-01-292-2349

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-292-2349 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.290 inches **Overall Height:** Between 1.792 inches and 1.832 inches **Overall Width:** Between 1.792 inches and 1.832 inches **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Distance From Mounting Shoulder To Front Face:** Between 0.785 inches and 0.790 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 26.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.290 inches Thready Qty Per Inch (tpi): **Thread Size:** 1.438 inches **Shell Material:**

Cadmium

Aluminum alloy

Shell Surface Treatment:

NSN 5935-01-292-2349

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Test Data Document:

type data in specification type data on certain etc.).

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general
environmental and performance requirements and test conditions that are shown as "typical", "average", "", e
Thread Series Designator:
Unef
Specification Data:
96906-ms27656 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.