## NSN 5935-01-292-8135

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-292-8135

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.415 inches and 2.435 inches

**Overall Height:** 

Between 0.315 inches and 0.325 inches

**Overall Width:** 

Between 0.345 inches and 0.350 inches

**Environmental Protection:** 

Shock resistant and vibration proof and moisture resistant

**Mating End Quantity:** 

4

#### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

## **Contact Removability:**

Nonremovable single mating end 1st contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end 1st contact grouping

## **Connector Locking Method:**

Friction

## **Terminal Location:**

Back single mating end 1st contact grouping

## **Contact Material:**

Copper alloy 172 single mating end 1st contact grouping

## **Contact Surface Treatment:**

Gold single mating end 1st contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end 1st contact grouping

## **Terminal Type:**

Solder well single mating end 1st contact grouping

## **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end 1st contact grouping

## **Insert Material Specification:**

Mil-p-46174, cl 40, gr e military specification single material response single mating end

## **Included Contact Quantity:**

48 single mating end 1st contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.048 gold grains, troy

# NSN 5935-01-292-8135

Electrical Plug Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.