

View Online at <https://aerobasegroup.com/nsn/5935-01-292-8142>

Thread Class:

2a

Thread Direction:

Right-hand

Overall Length:

0.548 inches

Overall Diameter:

0.375 inches

Distance From Mounting Shoulder To Front Face:

0.300 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

1260-01-208-6448 mast mounted sight

Thread Length:

0.145 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.312 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, class 2 military specification 1st treatment response single mating end all contact groupings and mil-c-14550 military specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Pin single mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204, class ii military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.