
Electrical Plug Connector - Page 1 of 2





**Body Style:** Straight shape w/strain relief **Overall Length:** 6.750 inches **Overall Diameter:** 4.250 inches **Cable Entrance Diameter:** Between 0.980 inches and 1.710 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** B4s single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 100.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cord grip **End Application:** Training set, electronic warfare an/mst-tiv **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Glass fiber single mating end and plastic polyester single mating end **Terminal Type:** 

Crimp and solder single mating end single contact grouping

## NSN 5935-01-292-9105

Electrical Plug Connector - Page 2 of 2



**Shell Material:** 

Copper alloy

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0