

View Online at <https://aerobasegroup.com/nsn/5935-01-292-9117>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

0.875 inches

Overall Height:

0.547 inches

Overall Width:

0.190 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

0.656 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

9 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification all material responses single mating end or mil-p-19833, type gdi-30f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-female and location-left hand and jackscrew type-male and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.