Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-293-0502

#### **Body Style:**

Right angle type

### **Overall Length:**

1.198 inches

## **Overall Width:**

0.419 inches

#### **Body Height:**

0.479 inches

#### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

0.979 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate glass filled single mating end and plastic polyester glass filled single mating end

# **Terminal Type:**

Printed circuit single mating end single contact grouping

## Shell Material:

Metal

# Included Contact Quantity:

9 single mating end single contact grouping



# Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.009 gold grains, troy

# Precious Material:

Gold

# Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-24308/23 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A039b0