Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-293-2031

hread Class:
a
hread Direction:
light-hand
Body Style:
Straight shape, external coupling
Overall Length:
.320 inches
Overall Height:
Between 1.542 inches and 1.582 inches
Overall Width:
Between 1.542 inches and 1.582 inches
Inthreaded Mounting Hole Diameter:
Between 0.123 inches and 0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
.250 inches
Distance From Mounting Shoulder To Front Face:
Between 0.815 inches and 0.820 inches
hreaded Device Type:
Back shell
Nating End Quantity:
Contact Position Arrangement Style:
4-18 single mating end
Contact Removability:
emovable single mating end single contact grouping
Polarization Method:
ceyway or multiple keyway
nsert Position In Deg:
8.0 and 30.0 and 330.0 and 342.0
Shell Type:
Solid
Connector Locking Method:
ayonet pin
hread Length:
.219 inches
hready Qty Per Inch (tpi):
8
hread Size:
.188 inches



Back single m	ating end single contact grouping
Contact Mate	
Copper alloy s	ingle mating end single contact grouping
Contact Surfa	ace Treatment:
Gold single ma	ating end single contact grouping and copper single mating end single contact grouping
Terminal Type	e:
Crimp single n	nating end single contact grouping
Shell Material	
Aluminum allo	у
Shell Surface	Treatment:
Passivate	
Included Con	tact Quantity:
4 single mating	g end single contact grouping
Included Con	tact Type:
Coaxial pin sir	ngle mating end single contact grouping
Precious Mate	erial And Location:
Contact surfac	es gold
Precious Mate	erial And Weight:
0.020 gold gra	ins, troy
Precious Mate	erial:
Gold	
Thread Series	3 Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Measu	Jre:
Demilitarizati	on:
No	
Fiig:	
A039b0	