## NSN 5935-01-293-2226

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-293-2226 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.709 inches **Overall Diameter:** Between 2.046 inches and 2.078 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant **Distance From Mounting Shoulder To Front Face:** Between 0.879 inches and 0.910 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-96 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 319.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): **Thread Size:** 1.500 inches **Shell Material:** Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

## NSN 5935-01-293-2226

Electrical Receptacle Connector Body - Page 2 of 2



<b>Bushing Accommodation Hole Shape:</b>
Round w/flat
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A039b0