

View Online at <https://aerobasegroup.com/nsn/5935-01-293-3989>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.760 inches and 0.800 inches

Overall Height:

1.062 inches

Overall Width:

Between 1.245 inches and 1.255 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.964 inches and 0.974 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.964 inches and 0.974 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18

Thread Size:

1.062 inches

Insert Material:

Plastic epoxy single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-83723/61 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.