NSN 5935-01-293-7511

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-293-7511

| 2a and 2b |
|---|
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.719 inches |
| Overall Diameter: |
| 1.968 inches |
| Environmental Protection: |
| Heat resistant |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thready Qty Per Inch (tpi): |
| 18 and 18 |
| Thread Size: |
| 1.625 inches and 1.750 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic melamine mineral filled single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping |

NSN 5935-01-293-7511

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



| Terminal Type: |
|---|
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-b-750 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy 380.0 |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2 federal specification single treatment response |
| Shell Material Specification: |
| Qq-a-591, comp 2 federal specification single material response |
| Insert Material Specification: |
| Mil-m-14, type mme military specification single material response single mating end |
| Included Contact Quantity: |
| 48 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.048 gold grains, troy and 0.048 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unef and uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |