

View Online at <https://aerobasegroup.com/nsn/5935-01-293-7512>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape w/flange

**Overall Length:**

1.254 inches

**Overall Height:**

1.010 inches

**Overall Width:**

1.010 inches

**Environmental Protection:**

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.713 inches and 0.723 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.713 inches and 0.723 inches

**Distance From Mounting Shoulder To Front Face:**

0.508 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma 1st mating end

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

15000.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

36 and 24

**Thread Size:**

0.250 inches and 0.625 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550 military specification 2nd treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Gold and copper or passivate

**Shell Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response or qq-p-35 federal specification 2nd treatment response

**Shell Material Specification:**

Qq-s-764 federal specification single material response

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces and shell surface gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.