

View Online at <https://aerobasegroup.com/nsn/5935-01-293-7515>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Unable To Decode:**

Unable to decode and unable to decode

**Overall Length:**

Between 1.111 inches and 1.183 inches

**Overall Diameter:**

Between 1.714 inches and 1.746 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.786 inches and 0.818 inches

**Mounting Facility Thickness:**

Between 0.082 inches and 0.109 inches

**Threaded Device Type:**

Back shell and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-18 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Thread Size:**

0.812 inches and 1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Included Contact Quantity:**

18 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Connector is polarized in position c

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.018 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0