

View Online at <https://aerobasegroup.com/nsn/5935-01-294-3073>

**Body Material:**

Plastic

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Top or bottom mount w/molded saddle and bushing

**Overall Length:**

Between 1.700 inches and 1.740 inches

**Overall Height:**

0.630 inches

**Overall Width:**

Between 0.990 inches and 1.010 inches

**Mounting Hole Diameter:**

Between 0.142 inches and 0.152 inches

**Body Mounting Hole Accommodation Length:**

0.620 inches

**Body Mounting Hole Accommodation Width:**

Between 0.990 inches and 1.010 inches

**Mounting Hole Style:**

Rectangular, w/three mounting holes/slots

**Contact Material:**

Copper alloy

**Contact Surface Treatment:**

Gold

**Accommodated Contact Quantity:**

14

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 1.401 inches and 1.411 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 0.620 inches and 0.630 inches

**Thread Length:**

0.670 inches

**Polarization Type:**

Slot

**Projection Length Above Mounting Surface:**

Between 0.215 inches and 0.225 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Contact Position Arrangement Style:**

Irregular

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Furnished Items And Quantity:**

3 stud and 3 nut and 3 flat washer

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300