## NSN 5935-01-294-3687

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-294-3687 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.66 millimeters **Overall Height:** Between 42.6 millimeters and 43.2 millimeters **Overall Width:** Between 42.6 millimeters and 43.2 millimeters **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Center To Center Distance Between Mounting Facilities Parallel To Height:** 34.93 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 34.93 millimeters **Distance From Mounting Shoulder To Front Face:** 20.1 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-35 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 49.0 and 169.0 and 200.0 and 244.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 34.0 millimeters and 1.500 inches

1.00

**Thread Pitch In Millimeters:** 

## NSN 5935-01-294-3687

Electrical Receptacle Connector Body - Page 2 of 2



Plastic epoxy single mating end  Shell Material: Aluminum alloy  Shell Surface Treatment: Cadmium  Shell Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Tolerance Class: 6g external  Special Features: Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document: 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification Shelf Life: N/a	
Aluminum alloy  Shell Surface Treatment:  Cadmium  Shell Surface Treatment Specification:  Qq-p-416 federal specification single treatment response  Thread Tolerance Class: 6g external  Special Features:  Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Shell Surface Treatment:  Cadmium  Shell Surface Treatment Specification:  Qq-p-416 federal specification single treatment response  Thread Tolerance Class:  6g external  Special Features:  Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specif format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Cadmium  Shell Surface Treatment Specification:  Qq-p-416 federal specification single treatment response  Thread Tolerance Class: 6g external  Special Features:  Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Shell Surface Treatment Specification:  Qq-p-416 federal specification single treatment response  Thread Tolerance Class: 6g external  Special Features:  Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specif format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Qq-p-416 federal specification single treatment response  Thread Tolerance Class: 6g external  Special Features: Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document: 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification response to the commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	
Thread Tolerance Class: 6g external  Special Features: Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document: 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	
Special Features: Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document: 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specif format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	
Special Features:  Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specif format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Between mounting slot width 3.71 millimeters and 4.11 millimeters  Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specif format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
Test Data Document:  81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator:  Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificant; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data:  81349-dod-c-38999/20 government specification  Shelf Life:  N/a	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Thread Series Designator: Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	catior
Thread Series Designator: Iso m and special acme Specification Data: 81349-dod-c-38999/20 government specification Shelf Life: N/a	
Iso m and special acme  Specification Data: 81349-dod-c-38999/20 government specification  Shelf Life: N/a	
Specification Data: 81349-dod-c-38999/20 government specification Shelf Life: N/a	
81349-dod-c-38999/20 government specification  Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	