

View Online at https://aerobasegroup.com/nsn/5935-01-294-3689

Thread Class:	
2a	
Thread Direction	1:
Right-hand	
Body Style:	
Straight shape, e	external coupling
Overall Length:	
1.625 inches	
Overall Height:	
Between 1.798 in	ches and 1.838 inches
Overall Width:	
Between 1.798 in	ches and 1.838 inches
Environmental F	Protection:
Moisture resistan	t and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistar
Unthreaded Mou	Inting Hole Diameter:
Between 0.142 in	ches and 0.157 inches
Center To Cente	r Distance Between Mounting Facilities Parallel To Height:
1.392 inches	
Distance Betwee	en Centerlines Of Mounting Facilities Parallel To Body Width:
1.392 inches	
Distance From M	Nounting Shoulder To Front Face:
Between 0.878 in	ches and 0.898 inches
Threaded Device	э Туре:
Coupling facility	
Mating End Qua	ntity:
1	
Polarization Met	hod:
Keyway or multip	le keyway
Insert Position I	n Deg:
135.0 and 170.0 ;	and 200.0 and 310.0
Shell Type:	
Solid	
Connector Lock	ing Method:
Externally thread	ed shell
Thready Qty Per	Inch (tpi):
10	
Thread Size:	
1.625 inches	
Insert Material:	
Plastic fluorosilico	one single mating end
Shell Material:	
Aluminum	



Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0