NSN 5935-01-294-5779

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-294-5779

Body Style:

Single card

Overall Length:

Between 3.172 inches and 3.202 inches

Overall Height:

Between 0.715 inches and 0.735 inches

Overall Width:

0.627 inches

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 2.940 inches and 2.960 inches

Board Accommodated Length:

2.510 inches single board and 2.530 inches single board

Board Accommodated Width:

Between 0.084 inches and 0.104 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30 military specification all material responses single mating end

NSN 5935-01-294-5779

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 30 single mating end single contact grouping **Included Contact Type:** Leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.