NSN 5935-01-294-6579

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-294-6579

Body Style:
Straight shape
Overall Length:
2.270 inches
Overall Height:
0.669 inches
Overall Width:
0.351 inches
Environmental Protection:
Pressure proof and corrosion resistant and humidity resistant and heat resistant and cold resistant and vibration resistant and shock resistant
and fuel resistant and oil resistant and fungus resistant and dust resistant and sand resistant
Unthreaded Mounting Hole Diameter:
Between 0.091 inches and 0.101 inches
Distance Between Mounting Facility Centers:
Between 1.993 inches and 2.007 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end and guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 5 oclock and hexagon shape male post left-hand at 5 oclock

NSN 5935-01-294-6579

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-200/8 federal specification single material response or qq-a-250 federal specification single material response or qq-a-591 federal
specification single material response
Insert Material Specification:
Mil-m-14 military specification 1st material response single mating end and mil-m-24519 military specification 2nd material response single
mating end
Included Contact Quantity:
51 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.051 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.