## NSN 5935-01-294-7602

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-294-7602

**Body Style:** 

Straight shape, rectangular

**Overall Length:** 

Between 2.610 inches and 2.630 inches

**Overall Height:** 

Between 1.820 inches and 1.850 inches

Overall Width:

0.290 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.123 inches and 0.133 inches

**Distance Between Mounting Facility Centers:** 

Between 2.230 inches and 2.250 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:** 

40 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Special Features:** 

Furnished items - cable bracket

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.040 gold grains, troy

## NSN 5935-01-294-7602

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.