

View Online at <https://aerobasegroup.com/nsn/5935-01-294-9478>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.740 inches and 0.760 inches

Overall Diameter:

Between 0.480 inches and 0.520 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

Distance From Mounting Shoulder To Front Face:

Between 0.430 inches and 0.470 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

K all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36 and 32

Thread Size:

0.250 inches and 0.375 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.