

View Online at <https://aerobasegroup.com/nsn/5935-01-295-0154>

**Thread Class:**

2b and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.448 inches

**Overall Height:**

1.125 inches

**Overall Width:**

2.342 inches

**Environmental Protection:**

Thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.052 inches and 2.072 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

8 single mating end

**Polarization Method:**

Mating end and jackscrew

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

32 and 32 and 32

**Thread Size:**

0.138 inches and 0.138 inches and 0.138 inches

**Insert Material:**

Plastic diallyl phthalate single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Zinc and chromate

**Shell Surface Treatment Specification:**

Astm-b633 assn standard 1st treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Thread Series Designator:**

Uns and uns and uns

**Specification Data:**

10001-3255225 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.