NSN 5935-01-295-2244

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-2244

Straight shape
Overall Length:
2.150 inches
Overall Height:
0.490 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, class 0, grade c or d military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30f or sdg-f military specification all material responses single mating end

Unable To Decode:

Terminal Type:

Unable to decode and unable to decode

Solder well single mating end single contact grouping

NSN 5935-01-295-2244

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 26 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.