## NSN 5935-01-295-2245

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-2245

Body Style:
Straight shape
Overall Length:
1.541 inches
Overall Height:
4.355 inches
Overall Width:
2.000 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
4.026 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
3
Contact Position Arrangement Style:
"106, a106" 2nd mating end
Contact Removability:
Removable 3rd mating end 1st contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back 1st mating end single contact grouping
Contact Material:
Copper alloy 3rd mating end 1st contact grouping
Contact Surface Treatment:
Gold 2nd mating end single contact grouping
Insert Material:
Plastic diallyl phthalate all mating ends and glass fiber all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response 1st mating end single contact grouping

Terminal Type:

Crimp 3rd mating end 1st contact grouping

## NSN 5935-01-295-2245

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal
specification single material response
Insert Material Specification:
Mil-m-14, ty gdi-30f or sdg-f military specification 1st material response all mating ends and mil-m-14, type gdi-30f or sdg-f military
specification 2nd material response all mating ends or allied chemical 1288 bx mfr ref 3rd material response all mating ends or mil-m-14
military specification 4th material response all mating ends
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.241 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):