NSN 5935-01-295-2248



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-295-2248 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** Between 1.719 inches and 1.781 inches **Overall Width:** Between 1.719 inches and 1.781 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.843 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:**

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

NSN 5935-01-295-2248

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.500 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Nickel alloy single mating end 2nd contact grouping
Contact Surface Treatment:
Silver single mating end 5th contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold or contact surfaces silver
Precious Material And Weight:
0.050 gold grains, troy or 0.050 silver grains, troy
Precious Material:
Gold or silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0