

View Online at <https://aerobasegroup.com/nsn/5935-01-295-2251>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Pcb, external coupling

**Overall Length:**

0.670 inches

**Overall Height:**

0.312 inches

**Overall Width:**

0.312 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:**

0.051 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.280 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.280 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Smb single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2, gr c military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 22, 1/2 hard federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and copper

**Shell Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2, gr c military specification 1st treatment response and mil-c-14550, cl 4 military specification 2nd treatment response

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 hard federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-std-15504