NSN 5935-01-295-2256

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-2256

Thread Class:

2b and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.538 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Distance Between Mounting Facility Centers:

Between 2.396 inches and 2.416 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

100 single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

40 and 40 and 40

Thread Size:

0.112 inches and 0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end and plastic polyamide single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Steel

NSN 5935-01-295-2256

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0