## NSN 5935-01-295-2856

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-2856

**Body Style:** Straight shape **Overall Length:** Between 1.198 inches and 1.228 inches **Overall Height:** Between 0.479 inches and 0.509 inches Overall Width: 0.638 inches **Environmental Protection:** Heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 0.984 inches **Mating End Quantity: Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 300.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** 

Steel

## NSN 5935-01-295-2856

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, ty gdi-30f or sdg-f military specification all material responses single mating end
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Specification Data:
11263-65106 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.