

View Online at <https://aerobasegroup.com/nsn/5935-01-295-3336>

**Body Style:**

Square flange mount

**Environmental Protection:**

Cold resistant and heat resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

7 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

133.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**End Application:**

Facsimile set an/uxc-4

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping or silver single mating end single contact grouping

**Insert Material:**

Glass single mating end and plastic polyamide single mating end

**Shell Material:**

Aluminum alloy or zinc

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold or contact surfaces silver

**Precious Material And Weight:**

0.007 gold grains, troy or 0.007 silver grains, troy

**Precious Material:**

Gold or silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0