NSN 5935-01-295-3338

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-3338

view Online at https://aerobasegroup.com/nsn/0300-01-230-0000
Body Style:
Right angle type
Overall Length:
8.795 inches
Overall Width:
0.680 inches
Body Height:
0.390 inches
Environmental Protection:
Corrosion resistant and humidity resistant and shock resistant
Unthreaded Mounting Hole Diameter:
Between 0.124 inches and 0.130 inches
Distance Between Mounting Facility Centers:
8.475 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, gr c, cl 00 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Insert Material Specification:

Included Contact Quantity:150 single mating end single contact grouping

Mil-p-46161, gr b, cl 15 military specification single material response single mating end

NSN 5935-01-295-3338

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.150 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.