## NSN 5935-01-295-3359

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-3359 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.66 millimeters **Overall Height:** Between 23.5 millimeters and 24.1 millimeters **Overall Width:** Between 23.5 millimeters and 24.1 millimeters **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Center To Center Distance Between Mounting Facilities Parallel To Height:** 18.26 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 18.26 millimeters **Distance From Mounting Shoulder To Front Face:** 20.9 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13028 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 40.0 and 112.0 and 228.0 and 258.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 12.0 millimeters and 0.625 inches

1.00

**Thread Pitch In Millimeters:** 

## NSN 5935-01-295-3359

Electrical Receptacle Connector Body - Page 2 of 2



Insert Material:
Plastic epoxy single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g external
Special Features:
Between mounting slot width 3.05 millimeters and 3.45 millimeters
Test Data Document:
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-dod-c-38999/20 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0