AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-295-5003

view Online at https://aerobasegroup.com/nsn/5935-01-295-5003
Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.219 inches
Overall Diameter:
0.688 inches
Environmental Protection:
Pressure proof
Distance From Mounting Shoulder To Front Face:
0.828 inches
Mounting Facility Thickness:
0.188 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Contact Removability: Nonremovable single mating end single contact grouping
-
Nonremovable single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping
Nonremovable single mating end single contact grouping <b>Contact Maximum Ac Voltage Rating In Volts:</b> 500.0 single mating end single contact grouping <b>Shell Type:</b>
Nonremovable single mating end single contact grouping <b>Contact Maximum Ac Voltage Rating In Volts:</b> 500.0 single mating end single contact grouping <b>Shell Type:</b> Solid
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms:
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi):
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 and 28
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 and 28 Thread Size:
Nonremovable single mating end single contact grouping <b>Contact Maximum Ac Voltage Rating In Volts:</b> 500.0 single mating end single contact grouping <b>Shell Type:</b> Solid <b>Connector Locking Method:</b> Externally threaded shell <b>Radio Frequency Type Contact Characteristic Impedance In Ohms:</b> 50.0 single mating end single contact grouping <b>Thready Qty Per Inch (tpi):</b> 28 and 28 <b>Thread Size:</b> 0.438 inches and 0.500 inches
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 and 28 Thread Size: 0.438 inches and 0.500 inches
Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 and 28 Thread Size: 0.438 inches and 0.500 inches Terminal Location: Back single mating end single contact grouping

Silver single mating end single contact grouping and gold single mating end single contact grouping



**Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Copper alloy Shell Surface Treatment: Silver **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact and shell surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.105 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0