NSN 5935-01-295-6920

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-295-6920 **Thread Class:** 2g **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 9.976 inches **Overall Diameter:** Between 3.547 inches and 3.579 inches **Environmental Protection:** Humidity resistant and moisture resistant and corrosion resistant and shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** B4s single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 200.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 15.0 Shell Type: Potting **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): **Thread Size:** 3.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-295-6920Electrical Plug Connector - Page 2 of 2



| Contact Surface Treatment: |
|--|
| Silver single mating end single contact grouping |
| Insert Material: |
| Plastic phenolic single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Anodize |
| Shell Surface Treatment Specification: |
| Mil-a-8625, type 3 military specification single treatment response |
| Insert Material Specification: |
| Mil-m-14, ty mfh military specification single material response single mating end |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.020 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-14 spec. |
| |