## NSN 5935-01-296-0113

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-296-0113

**Body Style:** 

Right angle type

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Width:** 

0.711 inches

**Body Height:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.847 inches and 1.857 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

25 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**End Application:** 

Helicopter, cobra/tow, ah series; aircraft, f-16; missile, hellfire; b-52 aircraft; joint stars target radar; aircraft, airlifter c-17a; aircraft,

f-111; support, mx peacekeeper missile

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

**Terminal Type:** 

Pin single mating end single contact grouping

## NSN 5935-01-296-0113

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Metal
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, type sdg-f or type gpt-30f military specification 1st material response single mating end and mil-m-14, type sdg-f or type gpt-30f
military specification 2nd material response single mating end or mil-m-24519, type get-30f military specification 3rd material response single
mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/24 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.