## NSN 5935-01-296-1015

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-296-1015

**Body Style:** 

Pcb, external coupling

**Overall Length:** 

0.419 inches

**Overall Height:** 

0.156 inches

**Overall Width:** 

0.156 inches

**Environmental Protection:** 

Heat resistant and cold resistant and corrosion resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:** 

0.100 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.100 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

1.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

250.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:** 

12400.0 megahertz single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 1, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping

## NSN 5935-01-296-1015

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy 360
Shell Surface Treatment:
Gold
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
L-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):