

View Online at <https://aerobasegroup.com/nsn/5935-01-296-2189>

**Body Style:**

Straight shape

**Overall Length:**

Between 0.915 inches and 0.935 inches

**Overall Height:**

0.539 inches

**Overall Width:**

Between 0.288 inches and 0.308 inches

**Environmental Protection:**

Fungus resistant and vibration resistant and shock resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.088 inches and 0.096 inches

**Distance Between Mounting Facility Centers:**

Between 0.710 inches and 0.720 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, gr c, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy 6061 or aluminum alloy 380.0

**Shell Surface Treatment:**

Cadmium and chromate or zinc

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response or astm-b-633, ty ii assn standard 3rd treatment response

**Shell Material Specification:**

Qq-a-250/11 federal specification 1st material response or qq-a-591 federal specification 2nd material response

**Insert Material Specification:**

Mil-m-14, ty gdi-30f or ty sdg-f military specification all material responses single mating end

**Included Contact Quantity:**

15 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-83513 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-83513/02 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.