Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-296-2190

Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
34.16 millimeters	
Overall Height:	
Between 39.1 millimeters and 40.2 millimeters	
Overall Width:	
Between 39.1 millimeters and 40.2 millimeters	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
31.76 millimeters	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
31.76 millimeters	
Distance From Mounting Shoulder To Front Face:	
Between 19.2 millimeters and 20.8 millimeters	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
21-11 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
120.0 and 265.0	
Shell Type:	
Solid	
Connector Locking Method:	
Detent	
Thread Length:	
7.11 millimeters	
Thread Size:	
31.0 millimeters	
Thread Pitch In Millimeters:	
1.00	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	

Electrical Receptacle Connector - Page 2 of 2



**Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Tolerance Class:** 6g external **Included Contact Quantity:** 11 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.011 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** lso m Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.