

View Online at <https://aerobasegroup.com/nsn/5935-01-297-5919>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

34.16 millimeters

Overall Diameter:

49.89 millimeters

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

25-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

110.0 and 250.0

Shell Type:

Solid

Connector Locking Method:

Detent

Thread Size:

37.0 millimeters

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.061 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dos-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m

Specification Data:

81349-dod-c-38999/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.