Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-298-0164

Thread Direction.
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
34.16 millimeters
Overall Diameter:
31.15 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
13-4 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0 and 250.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
18.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize

# NSN 5935-01-298-0164

Electrical Plug Connector - Page 2 of 2



## Shell Surface Treatment Specification:

Mil-a-8625, type 3 military specification single treatment response

## Thread Tolerance Class:

6g external

# Included Contact Quantity:

4 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

# Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

## Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

lso m

Specification Data:

81349-dod-c-38999/49 government specification

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.