NSN 5935-01-298-0176

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-298-0176 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 41 number 20 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 26.0 and 156.0 and 208.0 and 276.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches

18

Thready Qty Per Inch (tpi):

NSN 5935-01-298-0176

Electrical Receptacle Connector - Page 2 of 3



| Thread Size: | |
|---|-------------|
| 1.188 inches | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping | |
| Insert Material: | |
| Plastic epoxy single mating end | |
| Contact Surface Treatment Specification: | |
| Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping | |
| Terminal Type: | |
| Crimp single mating end single contact grouping | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Cadmium | |
| Shell Surface Treatment Specification: | |
| Qq-p-416 federal specification single treatment response | |
| Shell Material Specification: | |
| Qq-a-367 federal specification single material response | |
| Included Contact Quantity: | |
| 41 single mating end single contact grouping | |
| Included Contact Type: | |
| Round pin single mating end single contact grouping | |
| Precious Material And Location: | |
| Contact surfaces gold | |
| Precious Material And Weight: | |
| 0.041 gold grains, troy | |
| Precious Material: | |
| Gold | |
| Test Data Document: | |
| 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in the specification type data | ecification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on co | ertain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Thread Series Designator: | |
| Unef | |
| Specification Data: | |
| 81349-mil-c-83723/72 government specification | |
| Shelf Life: | |
| N/a | |

Demilitarization:

Unit Of Measure:

NSN 5935-01-298-0176

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.