NSN 5935-01-298-0182

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-298-0182 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.062 inches **Overall Height:** 2.348 inches **Overall Width:** 2.348 inches **Environmental Protection:** Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** Between 0.168 inches and 0.183 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.734 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.734 inches **Distance From Mounting Shoulder To Front Face:** Between 1.410 inches and 1.430 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-155 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 67.0 and 164.0 and 218.0 and 280.0 **Shell Type:** Solid

Connector Locking Method:

Externally threaded shell

End Application:

Combat control acoustic an/bsy-1

Thread Length:

0.445 inches

NSN 5935-01-298-0182

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
10
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorosilicone single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate and nickel
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response
Included Contact Quantity:
155 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.155 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):