

View Online at https://aerobasegroup.com/nsn/5935-01-298-0440

Thread Clas	3.
2a	
Thread Dire	ction:
Right-hand	
Body Style:	
	pe, external coupling
Overall Leng	gth:
1.289 inches	
Overall Heig	jht:
Between 1.4	18 inches and 1.458 inches
Overall Widt	ih:
Between 1.4	18 inches and 1.458 inches
Unthreaded	Mounting Hole Diameter:
Between 0.1	23 inches and 0.138 inches
Center To C	enter Distance Between Mounting Facilities Parallel To Height:
1.156 inches	
Distance Be	tween Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches	
Distance Fro	om Mounting Shoulder To Front Face:
Between 0.8	15 inches and 0.820 inches
Threaded De	evice Type:
Back shell	
Mating End	Quantity:
1	
Contact Pos	sition Arrangement Style:
19-35 single	mating end
Polarization	Method:
Keyway or m	ultiple keyway
Insert Positi	on In Deg:
0.0	
Shell Type:	
Solid	
Connector L	Locking Method:
Bayonet pin	
Thread Leng	gth:
• 0.219 inches	-
	/ Per Inch (tpi):
18	
Thread Size	:
1.062 inches	
Shell Materi	
Aluminum all	

# NSN 5935-01-298-0440

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:

Nickel

## Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

### Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef

# Specification Data:

96906-ms27656 government standard

Shelf Life:

N/a

#### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.