# NSN 5935-01-298-1204

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-298-1204

**Body Style:** 

Straight type

**Overall Length:** 

Between 4.890 inches and 4.910 inches

**Overall Height:** 

0.739 inches

**Overall Width:** 

Between 0.390 inches and 0.410 inches

**Environmental Protection:** 

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

**Distance Between Mounting Facility Centers:** 

Between 4.640 inches and 4.660 inches

**Mating End Quantity:** 

1

## **Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

# **Connector Locking Method:**

Friction

#### **End Application:**

A/f-18-dcn

#### **Terminal Location:**

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic polyethylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-c-290, class 2 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment response single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# **Guide Design And Location:**

D shape pin left-hand at 9 oclock and d shape socket right-hand at 9 oclock

## **Insert Material Specification:**

Mil-m-24510 military enecification single material response single mating and

# NSN 5935-01-298-1204

Electrical Receptacle Connector - Page 2 of 2



Inclu	ded	Cont	act	Qua	ntity:

122 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.122 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.