

View Online at <https://aerobasegroup.com/nsn/5935-01-298-3439>

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

2.114 inches

**Body Height:**

0.252 inches

**Distance Between Mounting Facility Centers:**

1.800 inches

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Thread Size:**

2.5 millimeters

**Thread Pitch In Millimeters:**

0.45

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

29 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Pin protector included on this connector

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.029 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Iso s

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.